

Listing of Claims:

1. (currently amended) A method for enabling communication between video-enabled and non-video-enabled communication devices, the method comprising:

detecting a request to establish video communication between a first device and a second device;

determining that the second device is not capable of displaying a video signal;

establishing two-way audio communication between the first and second devices;

capturing video signals generated by the first device during the two-way audio communication;

in response to determining that the second device is not capable of displaying the captured video signals, caching the captured video signals for subsequent display after the two-way audio communication is concluded, wherein the captured video signals are not cached unless a determination is made that the second device is not capable of displaying the captured video signals.

2. (original) The method of claim 1, further comprising:

capturing audio signals generated by the first and second devices during the two-way audio communication; and

caching the captured audio signals.

3. (canceled).
4. (canceled).
5. (currently amended) The method of claim 66 [[1]], wherein the locator link comprises a Universal Resource Locator (URL).
6. (currently amended) The method of claim 66 [[1]], wherein caching comprises:
transmitting the locator link to a user of the second ~~non-video-enabled~~ device.
7. (original) The method of claim 6, wherein the locator link is transmitted to the user via a messaging system.
8. (previously presented) The method of claim 65, wherein the terminal comprises a display screen, the method further comprising:
displaying the video signals on the display screen of the terminal.
9. (original) The method of claim 2, further comprising:
receiving a request from a terminal to transmit the cached video and audio signals;
retrieving the cached video and audio signals from a storage device; and
transmitting the video and audio signals to the terminal.

10. (original) The method of claim 9, wherein the terminal comprises a display screen and a speaker, the method further comprising:

displaying the video signals on the display screen of the terminal; and
synchronously outputting the audio signals on the speaker of the terminal.

11. (original) The method of claim 1, wherein caching comprises:

encoding the video signals in a compressed format; and
storing the encoded video signals in a storage device.

12. (previously presented) The method of claim 11, wherein the compressed format comprises a form of predictive coding.

13. (original) The method of claim 11, wherein the storage device is selected from the group consisting of a magnetic storage device, an optical storage device, and a random access memory (RAM).

14. (original) The method of claim 1, wherein the first device comprises a camera for capturing video signals.

15. (original) The method of claim 1, wherein the first device is selected from the group consisting of a video-enabled telephone, a video-enabled cellular telephone,

a video-enabled personal computer, a video-enabled interactive television (ITV) system, and a video-enabled personal digital assistant (PDA).

16. (original) The method of claim 1, wherein the second device is selected from the group consisting of a non-video-enabled telephone, a non-video-enabled cellular telephone, a non-video-enabled personal computer, a non-video-enabled interactive television (ITV) system, and a non-video-enabled personal digital assistant (PDA).

17. (original) The method of claim 1, wherein the video signals are cached by a server coupled to the first and second devices by at least one network.

18. (previously presented) The method of claim 17, wherein the at least one network comprises at least one of a cable television network, a direct satellite broadcast (DBS) network, a wide-area network (WAN), a local-area network (LAN), a telephone network, and the Internet.

19. (original) The method of claim 17, wherein the server is located within a broadcast center associated with the at least one network.

20. (cancelled)

21. (currently amended) A system for enabling communication between video-enabled and non-video-enabled communication devices, the system comprising:

a request detection component configured to detect a request to establish video communication between a first device and a second device;

a video-enablement determination component configured to determine that the second device is not capable of displaying a video signal;

an audio communication component configured to establish two-way audio communication between the first and second devices;

a video capture component configured to capture video signals generated by the first device during the two-way audio communication;

a caching component configured to, in response to a determination being made that the second device is not capable of displaying the captured video signals, cache the captured video signals for subsequent display after the two-way audio communication is concluded, wherein the caching component does not cache the captured video signals unless a determination is made that the second device is not capable of displaying the captured video signals.

22. (original) The system of claim 21, further comprising:

an audio capture component configured to capture audio signals generated by the first and second devices during the two-way audio communication; and

wherein the caching component is further configured to cache the captured audio signals.

23. (canceled).

24. (canceled).

25. (currently amended) The system of claim 68 [[21]], wherein the locator link comprises a Universal Resource Locator (URL).

26. (currently amended) The system of claim 68 [[21]], wherein caching component is further configured to transmit the locator link to a user of the second ~~non-~~
~~video-enabled~~ device.

27. (original) The system of claim 26, wherein the locator link is transmitted to the user via a messaging system.

28. (previously presented) The system of claim 67, wherein the terminal comprises a display screen, the system further comprising:

a display component configured to display the video signals on the display screen of the terminal.

29. (previously presented) The system of claim 22, further comprising:

a request reception component configured to receive a request from a terminal to transmit the cached video and audio signals;

a transmission component configured to retrieve the cached video and audio signals from a storage device and to transmit the video and audio signals to the terminal.

30. (original) The system of claim 29, wherein the terminal comprises a display screen and a speaker, the system further comprising:

a display component configured to display the video signals on the display screen of the terminal; and

a speaker configured to synchronously output the audio signals.

31. (original) The system of claim 21, wherein the caching component comprises:

an encoder configured to encode the video signals in a compressed format; and

a storage device configured to store the encoded video signals.

32. (previously presented) The system of claim 31, wherein the compressed format comprises a form of predictive coding.

33. (original) The system of claim 31, wherein the storage device is selected from the group consisting of a magnetic storage device, an optical storage device, and a random access memory (RAM).

34. (original) The system of claim 21, wherein the first device comprises a camera for capturing video signals.

35. (original) The system of claim 21, wherein the first device is selected from the group consisting of a video-enabled telephone, a video-enabled cellular telephone, a video-enabled personal computer, a video-enabled interactive television (ITV) system, and a video-enabled personal digital assistant (PDA).

36. (original) The system of claim 21, wherein the second device is selected from the group consisting of a non-video-enabled telephone, a non-video-enabled cellular telephone, a non-video-enabled personal computer, a non-video-enabled interactive television (ITV) system, and a non-video-enabled personal digital assistant (PDA).

37. (original) The system of claim 21, wherein the video signals are cached by a server coupled to the first and second devices by at least one network.

38. (previously presented) The system of claim 37, wherein the at least one network comprises at least one of a cable television network, a direct satellite broadcast (DBS) network, a wide-area network (WAN), a local-area network (LAN), a telephone network, and the Internet.

39. (original) The system of claim 37, wherein the server is located within a broadcast center associated with the at least one network.

40. (cancelled)

41. (currently amended) A computer-readable storage medium comprising program code for causing a computer to perform a method for enabling communication between video-enabled and non-video-enabled communication devices, the method comprising:

detecting a request to establish video communication between a first device and a second device;

determining that the second device is not capable of displaying a video signal;

establishing two-way audio communication between the first and second devices;

capturing video signals generated by the first device during the two-way audio communication;

in response to determining that the second device is not capable of displaying the captured video signals, caching the captured video signals for subsequent display after the two-way audio communication is concluded, wherein the captured video signals are not cached unless a determination is made that the second device is not capable of displaying the captured video signals.

42. (previously presented) The computer-readable storage medium of claim 41, further comprising:

capturing audio signals generated by the first and second devices during the two-way audio communication; and
caching the captured audio signals.

43. (canceled).

44. (canceled).

45. (currently amended) The computer-readable storage medium of claim 70 [[41]], wherein the locator link comprises a Universal Resource Locator (URL).

46. (currently amended) The computer-readable storage medium of claim 70 [[41]], wherein caching comprises:

transmitting the locator link to a user of the second ~~non-video-enabled~~ device.

47. (previously presented) The computer-readable storage medium of claim 46, wherein the locator link is transmitted to the user via a messaging system.

48. (previously presented) The computer-readable storage medium of claim 69, wherein the terminal comprises a display screen, the method further comprising:

displaying the video signals on the display screen of the terminal.

49. (previously presented) The computer-readable storage medium of claim 42, the method further comprising:

receiving a request from a terminal to transmit the cached video and audio signals;

retrieving the cached video and audio signals from a storage device; and
transmitting the video and audio signals to the terminal.

50. (previously presented) The computer-readable storage medium of claim 49, wherein the terminal comprises a display screen and a speaker, the method further comprising:

displaying the video signals on the display screen of the terminal; and
synchronously outputting the audio signals on the speaker of the terminal.

51. (previously presented) The computer-readable storage medium of claim 41, wherein caching comprises:

encoding the video signals in a compressed format; and
storing the encoded video signals in a storage device.

52. (previously presented) The computer-readable storage medium of claim 51, wherein the compressed format comprises a form of predictive coding.

53. (previously presented) The computer-readable storage medium of claim 51, wherein the storage device is selected from the group consisting of a magnetic storage device, an optical storage device, and a random access memory (RAM).

54. (previously presented) The computer-readable storage medium of claim 41, wherein the first device comprises a camera for capturing video signals.

55. (previously presented) The computer-readable storage medium of claim 41, wherein the first device is selected from the group consisting of a video-enabled telephone, a video-enabled cellular telephone, a video-enabled personal computer, a video-enabled interactive television (ITV) system, and a video-enabled personal digital assistant (PDA).

56. (previously presented) The computer-readable storage medium of claim 41, wherein the second device is selected from the group consisting of a non-video-enabled telephone, a non-video-enabled cellular telephone, a non-video-enabled personal computer, a non-video-enabled interactive television (ITV) system, and a non-video-enabled personal digital assistant (PDA).

57. (previously presented) The computer-readable storage medium of claim 41, wherein the video signals are cached by a server coupled to the first and second devices by at least one network.

58. (previously presented) The computer-readable storage medium of claim 57, wherein the at least one network comprises at least one of a cable television network, a direct satellite broadcast (DBS) network, a wide-area network (WAN), a local-area network (LAN), a telephone network, and the Internet.

59. (previously presented) The computer-readable storage medium of claim 57, wherein the server is located within a broadcast center associated with the at least one network.

60. (cancelled)

61. (currently amended) A method for enabling communication between an interactive television system and non-video-enabled communication device, the method comprising:

detecting a request to establish video communication between the interactive television system and the non-video-enabled communication device;

determining that the non-video-enabled communication device is not capable of displaying a video signal;

establishing two-way audio communication between the interactive television system and the non-video-enabled communication device;

capturing video signals generated by the interactive television system during the two-way audio communication;

capturing audio signals generated by the interactive television system and the non-video-enabled communication device during the two-way audio communication;

in response to determining that the non-video-enabled communication device is not capable of displaying the captured video signals, caching the captured video and audio signals within a storage device for subsequent display and playback after the two-way audio communication is concluded, wherein the captured video signals are not cached unless a determination is made that the non-video-enabled communication device is not capable of displaying the captured video signals;

receiving a request from a terminal to transmit the cached video and audio signals;

retrieving the cached video and audio signals from the storage device; and

transmitting the video and audio signals to the terminal for display and playback thereon.

62. (currently amended) A system for enabling communication between an interactive television system and non-video-enabled communication device, the system comprising:

a request detection component configured to detect a request to establish video communication between the interactive television system and the non-video-enabled communication device;

a video-enablement determination component configured to determine that the non-video-enabled communication device is not capable of displaying a video signal;

an audio communication component configured to establish two-way audio communication between the interactive television system and the non-video-enabled communication device;

a video capture component configured to capture video signals generated by the interactive television system during the two-way audio communication;

an audio capture component configured to capture audio signals generated by the interactive television system and the non-video-enabled communication device during the two-way audio communication;

a caching component configured to, in response to a determination being made that the non-video-enabled communication device is not capable of displaying the captured video signals, cache the captured video and audio signals within a storage device for subsequent display and playback after the two-way audio communication is concluded, wherein the caching component does not cache the captured video signals unless a determination is made that the non-video-enabled communication device is not capable of displaying the captured video signals;

a request reception component configured to receive a request from a terminal to transmit the cached video and audio signals; and

a transmission component configured to retrieve the cached video and audio signals from the storage device and to transmit the video and audio signals to the terminal for display and playback thereon.

63. (currently amended) A system for enabling communication between video-enabled and non-video-enabled communication devices, the system comprising:

means for detecting a request to establish video communication between a first device and a second device;

means for determining that the second device is not capable of displaying a video signal;

means for establishing two-way audio communication between the first and second devices;

means for capturing video signals generated by the first device during the two-way audio communication;

means for caching, in response to determining that the second device is not capable of displaying the captured video signals, the captured video signals for subsequent display after the two-way audio communication is concluded, wherein the means for caching does not cache the captured video signals unless a determination is made that the second device is not capable of displaying the captured video signals.

64. (currently amended) A system for enabling communication between an interactive television system and non-video-enabled communication device, the system comprising:

means for detecting a request to establish video communication between the interactive television system and the non-video-enabled communication device;

means for determining that the non-video-enabled communication device is not capable of displaying a video signal;

means for establishing two-way audio communication between the interactive television system and the non-video-enabled communication device;

means for capturing video signals generated by the interactive television system during the two-way audio communication;

means for capturing audio signals generated by the interactive television system and the non-video-enabled communication device during the two-way audio communication;

means for, in response to determining that the non-video-enabled communication device is not capable of displaying the captured video signals, caching the captured video and audio signals within a storage device for subsequent display and playback after the two-way audio communication is concluded, wherein the means for caching does not cache the captured video signals unless a determination is made that the non-video-enabled communication device is not capable of displaying the captured video signals;

means for receiving a request from a terminal to transmit the cached video and audio signals;

means for retrieving the cached video and audio signals from the storage device; and

means for transmitting the video and audio signals to the terminal for display and playback thereon.

65. (previously presented) The method of claim 1, further comprising:

receiving a request from a terminal to transmit the cached video signals;

retrieving the cached video signals from a storage device; and

transmitting the video signals to the terminal.

66. (previously presented) The method of claim 65, wherein the request to transmit the cached video signals comprises a locator link indicating a stored location of the cached video signals.

67. (previously presented) The system of claim 21, further comprising:

a request reception component configured to receive a request from a terminal to transmit the cached video signals;

a transmission component configured to retrieve the cached video signals from a storage device and to transmit the video signals to the terminal.

68. (previously presented) The system of claim 67, wherein the request to transmit the cached video signals comprises a locator link indicating a stored location of the cached video signals.

69. (currently amended) The computer-readable storage medium ~~computer program-product~~ of claim 41, further comprising:

- receiving a request from a terminal to transmit the cached video signals;
- retrieving the cached video signals from a storage device; and
- transmitting the video signals to the terminal.

70. (currently amended) The computer-readable storage medium ~~computer program-product~~ of claim 69, wherein the request to transmit the cached video signals comprises a locator link indicating a stored location of the cached video signals.